

Pressure Washer Hose

113W Washdown (Specification 33213W)



Nom. I.D.		Nom. O.D.		Maxi. W.P.		Suction		Min. Bend Radius		Kg. Per	Standard Pack	Part No.
(In.)	(mm)	(In.)	(mm)	(psi)	(Mpa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(m.)	(m.)	
1/2"	12.7	0.91	23.0	200	1.37	15.0	381	3.0	76.2	0.44	100	3213-0601
3/4"	19.0	1.25	32.0	200	1.37	15.0	381	4.5	114.0	0.82	100	3213-0602
1"	25.4	1.53	39.0	200	1.37	15.0	381	6.0	152.4	1.10	100	3213-0603

Recommended for:

Hot water up to 100°C where steam is injected into the water for food handling or processing plant washdown service hose with a white cover and tube. Especially useful for dairy applications.

CAUTION: NOT RECOMMENDED FOR USE WITH PURE STEAM.

Temperature: -20°C to +100°C continuous service.

Construction:

Tube: Type P (EPDM). White.

Reinforcement: High tensile synthetic textile cord.

Cover: Type P (EPDM). White. All sizes are perforated.

Couplings: Gates GLX®

Packaging:

All sizes 100m per coil wrapped in PVC film.

Branding: Continuous ink print label.

Example:  113W Washdown 1 Inch (25.4mm) 200 PSI (1.38Mpa) WP

Standards: FDA Quality hose.

Steam Hose

232MB Steam Queen® (Specification 3602EL)



Nom. I.D.		Nom. O.D.		Maxi. W.P.		Suction		Min. Bend Radius		Kg. Per	Standard Pack	Part No.
(In.)	(mm)	(In.)	(mm)	(psi)	(Mpa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(m.)	(m.)	
3/8	9.5	0.80	20.3	250	1.72	30.0	762	4.0	102	0.46	15	3602-1051
3/8	9.5	0.80	20.3	250	1.72	30.0	762	4.0	102	0.46	91	3602-1061
1/2	12.7	1.02	25.9	250	1.72	25.0	635	7.0	178	0.73	15	3602-1052
1/2	12.7	1.02	25.9	250	1.72	25.0	635	7.0	178	0.73	91	3602-1062
3/4	19.1	1.27	32.3	250	1.72	20.0	508	9.0	229	0.95	15	3602-1055
3/4	19.1	1.27	32.3	250	1.72	20.0	508	9.0	229	0.95	91	3602-1065
1	25.4	1.52	38.6	250	1.72	20.0	508	11.0	279	1.18	15	3602-1057
1 1/2	38.1	2.18	55.4	250	1.72	10.0	254	20.0	508	1.84	15	3602-1059
2	50.8	2.66	67.6	250	1.72	10.0	254	25.0	635	3.34	15	3602-1060

Recommended for:

Steam Queen features a specially compounded, perforated synthetic rubber cover intended for use where the hose is exposed to oils, grease, fats, and similar materials.

It will handle all types of steam - saturated and superheated - up to 250 psi +232°C.

WARNING: DO NOT ALTERNATE USE BETWEEN STEAM AND WATER.

232MB is designed with a 10:1 safety factor.

Temperature: -40°C to +232°C continuous service.

Construction:

Tube: Type P₂ (EPDM). Black.

Reinforcement: Braided, high tensile steel wire.

3/8" & 1/2": one-braid.

3/4" thru 2": two-braid.

Cover: Type B₁ (special compound designed to withstand heat and oil). Red. All sizes are perforated.

Packaging:

15m lengths: Coiled in a carton.

3/8" through 3/4": Packaged in 60m to 91m reels.

Maximum of 3 pieces. Minimum length 7m. One length under 30m.

Branding: Continuous moulded brand.

Example:  232MB Steam Queen® 3/4 Inch 2 Wire Braid 250 PSI WP at 450°F Degrees F Made In U.S.A.

Caution: Tighten Clamps Before Using.

Standards:

Cover: RMA (Class C) Limited oil resistance.